

ROLLING DOOR PRODUCTS



Model 800

- » SERVICE DOORS
- » FIRE DOORS
- » SECURITY GRILLES

- » COUNTER SHUTTERS
- » SECURITY SHUTTERS

COMMERCIAL DOORS

The Wayne Dalton line of Rolling Door Systems features service doors, fire doors, security shutters, counter shutters and grilles designed to fit a wide range of applications. In many instances a specific application calls for a specialized door that doesn't quite fit one of our standard models. These situations are an ideal time to call on our highly skilled product team for assistance.

Our Rolling Door customer service managers and engineers can assist you in identifying precisely what your needs are and whether modifying a standard door design to meet your criteria would be feasible. From engineering oversized doors to modifying doors to accommodate pass-doors or other obstructions, our team has a great deal of experience at customizing doors to meet our customers' unique needs.

For more information, including detailed drawings, specifications and other technical information, contact the Wayne Dalton Rolling Door Group at 800-764-1457 or visit us online at wayne-dalton.com/commercial.



FireStar® Model 700C

ROLLING DOOR PRODUCTS

Use this guide to help determine which doors might be best for your specific application. Each door model offers a variety of sizes, options and custom configurations. Larger sizes may be available. Contact Wayne Dalton Rolling Door Group for more information.

MODEL	MAXIMUM WIDTH	MAXIMUM HEIGHT	FIRE LABELED	WIND LOAD RATED	CONSTRUCTION
SERVICE DOORS					
Models 800 ADV/800C ADV	20'0"	20'0"	--	20 psf is standard, greater is an option	Steel, Aluminum, Stainless Steel
Model 800C ThermoTite™ (Insulated)	42'0"	30'0"	--	20 psf is standard, greater is an option	Steel, Aluminum, Stainless Steel
Model 800 (Optional Secur-Vent® Ventilated Slats)	40'0"	40'0"	--	20 psf is standard, greater is an option	Steel, Aluminum, Stainless Steel
Model 900	14'0"	14'0"	--	20 psf is standard, greater is an option	Steel, Aluminum, Stainless Steel
Model 926	12'0"	12'0"	--	20 psf is standard, greater is an option	26-gauge Galvanized Steel
FIRE-RATED DOORS AND COUNTER SHUTTERS					
FireStar® Model 700C Fire Door (Insulated)	24'0"	24'0"	Yes	Optional	Steel, Stainless Steel
FireStar® Model 700 Fire Door	36'0"	28'0"	Yes	Optional	Steel, Stainless Steel
FireStar® Model 540/550 Counter Shutter	16'0"	9'0"	Yes	--	Galvanized Steel (540), Stainless Steel (550)
SECURITY GRILLES					
Model 600 ADV Advanced Rolling Grille System	30'4"	14'4"	--	--	Steel, Aluminum, Stainless Steel
Model 600 Rolling Grille (Optional Emergency Egress)	42'0"	20'0"	--	--	Steel, Aluminum, Stainless Steel
Accordion Folding Grille	No Limit	14'0"	--	--	Aluminum
COUNTER SHUTTERS					
Model 500	15'0"	7'0"	--	--	Steel, Aluminum, Stainless Steel
Wood Counter Shutters	12'0"	8'0"	--	--	Various woods
Integral Frame (available with fire rated option)	12'0"	6'0"	Optional	--	Steel, Aluminum, Stainless Steel
SECURITY SHUTTERS					
Model 523	20'0"	14'0"	--	--	Aluminum



Model 800 ADV

COMMERCIAL DOORS

MODELS 800 ADV/800C ADV ROLLING SERVICE DOORS

Models 800 ADV/800C ADV are three times faster than standard rolling steel doors.

- Opening speed of 24" per second and closing speed of 12" per second
- Rated for design pressure of +/- 20 psf standard. Higher psf ratings are available
- Springless direct drive design provides smooth, reliable, high cycle operation
- Wireless safety edge reverses downward motion upon impact



MODEL 800C THERMOTITE™ ROLLING SERVICE DOORS

The Thermotite 800C is an insulated, energy efficient door with standard sizes up to 42' wide and 30' high.

- Wind load ± 20 psf standard. Higher psf ratings are available
- R-value = 7.7
- Polyurethane foamed-in-place insulation, 3" flat slats



MODEL 800 ROLLING SERVICE DOORS

Designed for strength and durability, Wayne Dalton's Model 800 doors are available in a variety of materials, slat profiles and colors.

- Maximum width 40'0"; maximum height 40'0"
- Wind load ± 20 psf standard. Higher psf ratings are available
- Heavy-duty 3" flat and curved slats available
- Additional options include Secure-Vent and Titan slats



MODEL 900 ROLLING SERVICE DOORS

Designed to provide strength and durability in openings up to 14' x 14'.

- Wind load ± 20 psf standard on most size and slat gauges
- 2" flat and curved slats available
- Available in Gray, White, Beige or Brown



ROLLING DOOR PRODUCTS



MODEL 926 ROLLING SERVICE DOOR

Model 926 doors provide an economical yet durable solution for everything from self-storage to industrial openings.

- Maximum width 12'0"; maximum height 12'0"
- Wind load ± 20 psf standard
- 2" flat slats
- Galvanized steel



FIRESTAR® MODEL 700/700C ROLLING FIRE DOORS

Ideal for commercial and industrial interior applications, these doors provide a practical solution to safety and fire protection.

- Model 700C maximum width 24'0"; maximum height 24'0"
- Model 700 (uninsulated) maximum width 36'0", height 28'0"
- Model 700C features mineral wool insulation which provides an R-value of 5.0
- UL fire-rated labels up to 4 hours (FM labels available)
- Compact design for maximum access through opening
- Release system ties into the building's fire system



FIRESTAR® MODEL 540/550 FIRE-RATED COUNTER SHUTTER

FireStar® Fire-Rated Counter Shutters are equally suitable for commercial or industrial applications. They can also perform double duty providing protection against fire and security for every day use.

- Maximum width 16'0"; maximum height 9'0"
- UL fire-rated label (FM label available)
- Steel (540) and Stainless Steel (550) available
- Release system ties into the building's fire system
- Fire-rated counter tops optional



MODEL 600 ADV ROLLING GRILLES

Ideal applications are high cycle or high traffic areas such as parking garages, industrial manufacturing facilities, government and public facilities and shipping and receiving docks.

- Opening speed of 24" per second and closing speed of 12" per second
- Strong grille construction for longer curtain life
- Three times faster than standard rolling grilles
- Springless direct drive design provides smooth, reliable, high cycle operation
- Wireless safety edge reverses downward motion upon impact

COMMERCIAL DOORS

Model 600 Rolling Grilles

Ideal for retail, as well as other commercial and industrial applications, Model 600 provides security combined with visibility and ventilation.

- Maximum width 42'0"; maximum height 20'0"
- Many available options, including: materials, operation, finishes, curtain patterns, emergency egress and locking
- Durable design provides for longer life
- Compact design for maximum access through opening



Accordion Grilles

Wayne Dalton Accordion Grilles combine beauty, security, design flexibility with the economy of side-stacking and manual operation.

- Perforated steel panels for full ventilation
- Clear polycarbonate panels for visual access and durability
- Full-height aluminum curtain for maximum security



Model 500 Rolling Counter Shutters

Designed for interior or exterior use, Model 500 Rolling Counter Shutters feature rugged construction that provides maximum security.

- Compact design
- Comprised of extruded aluminum, roll-formed galvanized steel or stainless steel slats
- Aesthetically pleasing



Wood Counter Shutters

Available in a variety of wood species, these counter shutters provide security with a warm, finished appearance.

- Available in Red Oak, White Oak, Birch, Mahogany, Pine, Cherry and other hardwoods
- Ideal for interior counters, check rooms, ticket offices and other service locations
- Compact design
- Natural beauty



ROLLING DOOR PRODUCTS



Integral Frame Counter Shutters and Integral Frame Fire Counter Shutters

These counter doors are complete with frame and sill and carry a UL fire rated label* where necessary. Shipped factory-welded and fully assembled.

- Steel, stainless steel, or aluminum
- Built-in or slip-in unit
- Easy installation

*Steel and stainless steel



Model 523 Rolling Security Shutters

Wayne Dalton's Model 523 has a compact design and comes pre-assembled for easy installation in areas with low headroom and side room requirements.

- Standard sizes up to 20' wide and 14' high
- Manual, crank or motorized operation
- Aluminum construction
- Extruded aluminum slats

Genie Commercial Operators



The Genie Commercial Line of industrial door operators meets the requirements of the most demanding applications.

- Available in medium, standard and heavy-duty
- Operating types include hoist, jackshaft and sidemount trolley
- Horsepower options include 1/2, 3/4, 1 and 3 HP

For more information, visit the Genie Commercial website at commercial.geniecompany.com

Fire Door Release Device



This device controls the release of the door in a fire emergency and provides protection for both people and property.

- Adjustable time delay
- Optional horn, strobe light or voice annunciator
- Optional battery backup system provides protection even in power outages

ARCAT.com

Features downloadable specifications, and dozens of detail drawings available in a variety of formats, ARCAT also offers their SpecWizard™ service to help you build a custom specification. Simply type Wayne Dalton into the search box on the home page to access our technical information at ARCAT.com.

SWEETS.com®

You'll find Wayne Dalton in the manufacturer directory at SWEETS.com. Our full specifications and CAD files are available on the SWEETS website.



Model 600 ADV



Architect Resource Center

Visit wayne-dalton.com/architect-resource-center to find our Architect Resource Center. In this tool, you will quickly find all of the specifications, drawings and documents you need to complete your project.

Wayne Dalton
COMMERCIAL DOORS

DISTRIBUTED BY:

2501 S. State Hwy 121 Bus., Ste 200
Lewisville, TX 75067

wayne-dalton.com



© 2017 Wayne Dalton, a Division of Overhead Door Corporation. Consistent with our policy of continuing product improvement, we reserve the right to change product specifications without notice or obligation. Item 333065 06/2017