



Roll-Up Sheet Doors



WAYNE DALTON COMMERCIAL DOORS

- ▶ 790-CW COMMERCIAL WIND LOAD DOOR
- ▶ 780-CD COMMERCIAL DOOR
- ▶ 770-SS SELF STORAGE DOOR

Wayne Dalton's Roll-up Sheet Door offers the perfect solution when your project requires an attractive and solidly constructed roll-up sheet door that is also easy on your budget.

These doors incorporate innovative design elements that enable fast installation and ensure smooth operation for enhanced door life.

- 26-gauge, roll-formed galvanized steel curtain enhances strength and maximizes wind load performance
- Unique curtain profile facilitates smooth operation and minimizes curtain damage
- Stepped rings allow tight, uniform curtain wrap and minimize headroom requirements
- Bearings prevent steel-to-steel contact, improve door operation and increase door shaft life
- 790-CW commercial door sizes to 20' wide by 16' high (6096 mm by 4877 mm)
- 780-CD commercial door sizes to 16' wide by 16' high (4877mm by 4877mm)
- 770-SS self-storage door sizes from 3' wide by 7' high (914 mm by 2134 mm) up to 10' wide by 10' high (3048 mm by 3048 mm)

Color Options



White



Glossy White



Royal Blue



Polar Blue



Forest Green



Desert Tan



Dark Teal



Teal



Walnut Brown



Bronze



Garnet Red

Actual colors may vary from brochure due to fluctuations in the printing process. Always request a color sample from your Dealer for accurate color matching.

Options

- Genie® commercial operator (GCL-MJ or GCL-MH) available on 790-CW and 780-CD
- Chain hoist with reduced drive, non-handed quick-connect components standard on some 790-CW and 780-CD doors, depending upon size
- Curtain lock; two-bolt, double shackle lock or cylinder lock 790-CW and 780-CD
- Jamb extension brackets for steel/wood jambs available on 790-CW and 780-CD
- Header draft seal



Shown here:
GCL-MH Operator

ROLL-UP SHEET DOORS



Model 790-CW

- Max. standard width 20' (6096 mm)
- Max. standard height 16' (4877 mm)
- Counterbalance assembly 12" (305 mm), steel stepped rings to minimize headroom and enhance door operation
- Wind load – integrated curtain wind locks and guide to withstand wind load to minimum design pressures of 22/-22 psf (107/-107 kgf/sq m)
- Universal guides 14-gauge, roll-formed galvanized steel with pre-punched through-hole design for mounting to concrete, masonry, steel or wood jambs
- Headplate – 11-gauge steel
- Bottom bar – extruded aluminum reinforced with steel, roll-formed angles



Model 780-CD

- Max. standard width 16' (4877 mm)
- Max. standard height 16' (4877 mm)
- Counterbalance assembly 12" (305 mm), steel stepped rings to minimize headroom and enhance door operation
- Universal guides – 18-gauge, roll-formed galvanized steel with pre-punched through-hole design for mounting to concrete, masonry, steel or wood jambs
- Headplate – 11-gauge steel
- Bottom bar – Extruded aluminum reinforced with steel, roll-formed angles
- Lock – Dual slide-bolt locks on bottom bar



Model 770-SS

- Max. standard width 10' (3048 mm)
- Max. standard height 10' (3048 mm)
- Counterbalance assembly 9" (229 mm), steel stepped rings to minimize headroom and enhance door operation
- Universal guides – 18-gauge, roll-formed galvanized steel with pre-punched through-hole design for mounting to concrete, masonry, steel or wood jambs
- Headplate – 11-gauge steel
- Quick-connect bottom bar stop – 14-gauge galvanized steel, with roller bearings
- Lock – Right-side, two-bolt, yellow Dichromate Super Seal curtain lock

Model	Max Width	Max Height	Application-Duty	Steel Gauge
790-CW	20'0" (6096 mm)	16'0" (4877 mm)	Commercial/ Wind load	26-Gauge Steel
780-CD	16'0" (4877 mm)	16'0" (4877 mm)	Commercial	26-Gauge Steel
770-SS	10'0" (3048 mm)	10'0" (3048 mm)	Self Storage	26-Gauge Steel

FOR TECHNICAL INFORMATION, VISIT WWW.WAYNE-DALTON.COM/COMMERCIAL

Architect Resource Center

www.wayne-dalton.com/commercial

Go to www.wayne-dalton.com/commercial and click on the Architect Resource Center. Here you will quickly find all of the specifications, drawings and documents you need to complete your project.



DISTRIBUTED BY: