



MODEL 926

ROLLING STEEL SERVICE DOOR



WAYNE DALTON COMMERCIAL DOORS

Medium-Duty Rolling Steel Service Door

An economical, secure solution to protect facility openings. Options are available to customize to your facilities needs.

With numerous innovations and years of experience, Wayne Dalton continues to lead all other manufacturers with both standard and custom-made doors from a variety of materials and colors to meet almost any need.

➤ SIZES UP TO 12' WIDE AND 12' HIGH

➤ GALVANIZED STEEL CONSTRUCTION

➤ 26-GAUGE FLAT SLATS



MODEL 926

Standard Features Overview

- Sizes up to 12' wide and 12' tall
- Face mount or between jambs
- 26-gauge, #17 slats are 2" flat style profile, constructed of hot-dipped galvanized steel with polyester primer and baked on white polyester top coat paint finish
- Zinc-plated steel endlocks, fastened to both ends of alternate slats
- Constructed to withstand 20 PSF wind load
- Roll-formed 1/8" thick steel channel guides (G guides) and 3/16" thick steel wall angles comprise the guide assembly
- Counterbalance barrel assembly is made from 4" steel pipe and helical torsion springs designed for 20,000 cycles with cast iron spring fittings
- Bottom bar assembly is constructed from galvanized steel, double angle design with bottom astragal
- Slide bolts standard on push up; padlockable chain keeper on chain hoist
- Push up, manual operation

Options

- Vinyl weatherseal for curtain, lintel brush, and rubber hood baffle
- Powder coat
- Manual chain hoist
- Motor operator
- Pneumatic or electric sensing edge
- Wind locks
- End covers and fascia

The Model 926 Rolling Steel Service Door provides an economical and durable solution for self-storage to industrial openings.

Designed for Durability

Wayne Dalton Rolling Doors have a long history of excellence in design and construction that has met and often exceeded the needs and expectations of even the most critical projects.

Model 926 Rolling Service Doors are composed of flat-faced slats that provide a natural water shed and help reduce corrosion.

The slats are designed with free-acting interlocking joints that permit easy articulation when the door coils.

The door features a strong double-angle bottom bar reinforcing the lower edge of the curtain against wind pressure and permitting varied lock, astragal and safety edge options.

This bottom bar is designed for easy installation and does not require fasteners protruding into the guide openings, so the bottom bar does not interfere with door operation. Zinc-plated, cast iron windlocks add strength and prevent lateral slat movement.

FOR TECHNICAL INFORMATION, VISIT WWW.WAYNE-DALTON.COM/COMMERCIAL

Architect Resource Center

www.wayne-dalton.com/commercial

Go to www.wayne-dalton.com/commercial and click on the Architect Resource Center. Here you will quickly find all of the specifications, drawings and documents you need to complete your project.



DISTRIBUTED BY:

©2015 Wayne Dalton, a division of Overhead Door Corporation. Consistent with our policy of continuing product improvement, we reserve the right to change product specifications without notice or obligation. Item 343363 5M 09/15 JAR