



Dimension Charts for Model 523 Security Shutters

Model 523 Face of Wall Mounted

Slat Data

Slat	Opening Width	Standard
523 slat	Up to 20'	.05" aluminum

Headroom Clearance Dimensions

Based on Bottom Bar Selection	Opening Height	+ BBar Height	+ Hood Height	+ Hood Mount
Compact Bottom Bar	Thru 8'0"	2"	7"	1.5"
Compact Bottom Bar	8'1" Thru 10'0"	2"	8"	1.5"
Compact Bottom Bar	10'1" Thru 12'0"	2"	9"	1.5"
Compact Bottom Bar	12'1" Thru 14'0"	2"	10"	1.5"
Cylinder Locking Bottom Bar	Thru 8'0"	3.5"	7"	1.5"
Cylinder Locking Bottom Bar	8'1" Thru 10'0"	3.5"	8"	1.5"
Cylinder Locking Bottom Bar	10'1" Thru 12'0"	3.5"	9"	1.5"
Cylinder Locking Bottom Bar	12'1" Thru 14'0"	3.5"	10"	1.5"

Extruded Aluminum Guide Clearance Dimensions

Dimensions	Max Door Opening Width 20'
Guide Width	3.875"
Guide Width + Offset from edge of wall	3.875" + .375" =4.250"
Guide Depth	1.25"
Wall Tube standout req'd with cylinder lock	3"x1.50"



Dimension Charts for Model 523 Security Shutters

Model 523 Between Jamb Mounted

Slat Data

Slat	Opening Width	Standard
523 slat	Up to 20'	.05" aluminum

Headroom Clearance Dimensions

Based on Bottom Bar Selection	Opening Height	+ BBar Height	+ Hood Height
Compact Bottom Bar	Thru 8'0"	2"	7"
Compact Bottom Bar	8'1" Thru 10'0"	2"	8"
Compact Bottom Bar	10'1" Thru 12'0"	2"	9"
Compact Bottom Bar	12'1" Thru 14'0"	2"	10"
Cylinder Locking Bottom Bar	Thru 8'0"	3.5"	7"
Cylinder Locking Bottom Bar	8'1" Thru 10'0"	3.5"	8"
Cylinder Locking Bottom Bar	10'1" Thru 12'0"	3.5"	9"
Cylinder Locking Bottom Bar	12'1" Thru 14'0"	3.5"	10"

Extruded Aluminum Guide Clearance Dimensions

Dimensions	Max Door Opening Width 20'
Guide Width	3.875"
Guide Depth	1.25"