



- NOTES:
1. DOOR MODEL DS1001 IS INSULATED DS-100
 2. WHEN USING LOCK BY OTHERS (LBO), EXTENDED THROW SLIDE REQUIRED
 3. TOP DRAFT STOP OPTIONAL
 4. CURTAIN LOCK (CTL) HAND DETERMINED OUTSIDE LOOKING IN
 5. DIMENSIONS SHOWN ARE APPROXIMATE. SEE INSTALL MANUAL FOR EXACT COMPONENT LOCATION
 6. FASTENER SUBSTITUTION MUST BE REVIEWED AND APPROVED BY FACTORY PRIOR TO INSTALL

BRACKET TYPE	A
BEARING BRACKET	4-1/4"
TENSION-PRO BRACKET	5"

BRACKET TYPE	B
BEARING BRACKET	13"
TENSION-PRO BRACKET	14"
	16"

WINDLOAD RATING	POSITIVE DESIGN PRESSURE	NEGATIVE DESIGN PRESSURE
10'-0"	30PSF	34PSF

DS-100 WINDLOAD DOOR

CUSTOMER NAME _____

CUSTOMER NUMBER _____

PROJECT NAME _____

PROJECT LOCATION _____

CONTACT _____

PHONE NUMBER _____

FAX NUMBER _____

DATE _____

SALES ORDER NUMBER	DOOR MODEL	QTY	EXACT OPENING SIZE		OUTSIDE CURTAIN COLOR	JAMB TYPE		LH BRACKET TYPE			LOCK OPTIONS			OPTIONAL TOP DRAFT STOP?	OPTIONAL HOOD?	OTHER OPTIONS
			WIDTH	HEIGHT		MAS	STL	WOOD	BEARING	TENSION PRO	ISB BOTH	CTL RIGHT	CTL LEFT			
DS1001	DS1001															

Wayne Dalton
Door & Systems Div.
2589 County Rd 168
Dundee, Ohio 44624

SIZE DRAWING NO. **B 035-0027** REVISION **1**