



NOTES:

1. DOOR MODEL DS350I IS INSULATED DS-350
2. WHEN USING LOCK BY OTHERS (LBO), LONG THROW SLIDE REQUIRED
3. DOORS FOR OPENING SIZE GREATER THAN 10'-0" IN EITHER HEIGHT OR WIDTH USE T-BRACKET
4. TOP DRAFT STOP INCLUDED
5. OPER. HAND DETERMINED INSIDE LOOKING OUT
6. CURTAIN LOCK (CTL) HAND DETERMINED OUTSIDE LOOKING IN
7. DIMENSIONS SHOWN ARE APPROXIMATE. SEE INSTALL MANUAL FOR EXACT COMPONENT LOCATION
8. FASTENER SUBSTITUTION MUST BE REVIEWED AND APPROVED BY FACTORY PRIOR TO INSTALL

| METHOD OF OPERATION | A | B | C |
|--------------------------|----|-----|-----|
| PUSH-UP | 6" | 20" | 10" |
| DIRECT DRIVE CHAIN/MOTOR | 9" | 22" | 11" |
| REDUCED DRIVE CHAIN | 8" | 24" | 12" |

| METHOD OF OPERATION | A | B | C |
|--------------------------|--------------------|-----|-----|
| PUSH-UP | 6'-0" TO 8'-0" | 20" | 10" |
| DIRECT DRIVE CHAIN/MOTOR | 8'-1/4" TO 10'-0" | 22" | 11" |
| REDUCED DRIVE CHAIN | 10'-1/4" TO 16'-0" | 24" | 12" |

WINDLOAD RATING
(26GA PAINTED GALV. STEEL)

| MAXIMUM WIDTH | PANEL PROFILE | DESIGN PRESSURE |
|---------------|---------------|-----------------|
| 10'-0" | ROUND | ±37PSF |
| | SQUARE | ±44PSF |
| 12'-0" | ROUND | ±28PSF |
| | SQUARE | ±40PSF |
| 16'-0" | ROUND | ±28PSF |
| | SQUARE | ±34PSF |

| | | | | | | | | | | | | |
|--------------------|------------|-----|--------------------|-----------------------|--------------|---------------------|---------------|----------------|--------------|---------------|----------|----------|
| SALES ORDER NUMBER | DOOR MODEL | QTY | EXACT OPENING SIZE | OUTSIDE CURTAIN COLOR | JAMB TYPE | METHOD OF OPERATION | OPER. HAND | OPTIONAL HOOD? | LOCK OPTIONS | OTHER OPTIONS | | |
| DS350I | DS350I | | WIDTH HEIGHT | | MAS STL WOOD | PUSH DIRECT CHAIN | REDUCED CHAIN | MOTOR | ISB BOTH | CTL LEFT | CTL BOTH | LBO NONE |

DS-350 COMMERCIAL DOOR

CUSTOMER NAME _____

CUSTOMER NUMBER _____

PROJECT NAME _____

PROJECT LOCATION _____

CONTACT _____

PHONE NUMBER _____

FAX NUMBER _____

DATE _____

| | | |
|------|-------------|----------|
| SIZE | DRAWING NO. | REVISION |
| B | 035-0029 | 1 |

Wayne Dalton
Door & Systems Div.
2589 County Rd 168
Dundee, Ohio 44624