



**BOTTOM BAR DETAIL**

**BRACKET DETAIL**

**TOP DRAFT STOP DETAIL (OPTIONAL)**

- NOTES:**
1. DOOR MODEL DS75I IS INSULATED DS-75
  2. WHEN USING LOCK BY OTHERS (LBO), EXTENDED THROW SLIDE REQUIRED
  3. TOP DRAFT STOP OPTIONAL
  4. CURTAIN LOCK (CTL) HAND DETERMINED OUTSIDE LOOKING IN
  5. DIMENSIONS SHOWN ARE APPROXIMATE. SEE INSTALL MANUAL FOR EXACT COMPONENT LOCATION
  6. FASTENER SUBSTITUTION MUST BE REVIEWED AND APPROVED BY FACTORY PRIOR TO INSTALL

BRACKET TYPE	A	OPENING HEIGHT	B
BEARING BRACKET	4-1/4"	UP TO 6'8" HIGH	16"
TENSION-PRO BRACKET	5"	FROM 6'8-1/4" TO 8' HIGH	17"
		OVER 8' HIGH	18"

SALES ORDER NUMBER	DOOR MODEL	QTY	EXACT OPENING SIZE		OUTSIDE CURTAIN COLOR	JAMB TYPE		LH BRACKET TYPE	LOCK OPTIONS			OPTIONAL TOP DRAFT STOP?	OPTIONAL HOOD?	OTHER OPTIONS
	DS75		DS75I	WIDTH		HEIGHT	MAS		STL	WOOD	BEARING			

**DS-75 WINDLOAD DOOR**

CUSTOMER NAME \_\_\_\_\_

CUSTOMER NUMBER \_\_\_\_\_

PROJECT NAME \_\_\_\_\_

PROJECT LOCATION \_\_\_\_\_

CONTACT \_\_\_\_\_

PHONE NUMBER \_\_\_\_\_

FAX NUMBER \_\_\_\_\_

DATE \_\_\_\_\_

<b>WINDLOAD RATING</b>	MAXIMUM DOOR WIDTH	POSITIVE DESIGN PRESSURE	NEGATIVE DESIGN PRESSURE
	10'-0"	30PSF	34PSF



Wayne Dalton  
Door & Systems Div.  
2589 County Rd 168  
Dundee, Ohio 44624

SIZE DRAWING NO. B 035-0025

REVISION 1