



Quantum[®] 3214 1/2 HP Garage Door Opener

Specification Sheet



BETTER BY DESIGN

- Hot-dipped galvanized, double-angle trolley rail assembly for smooth operation.
- All-steel trolley with non-metallic glide surfaces has no metal-to-metal contact for smooth, efficient performance with a minimum of maintenance problems.
- Heavy duty, full-length chain for reliable operation and long life.
- Sleek, one-piece molded housing for quiet operation.
- Safer-by-design, high-efficiency motor with permanently lubed bearing and thermal overload protector for longer electronics and motor life.
- Wired infrared safety sensors add protection from injury or damage. Light beams will signal a clear opening unless beam is "broken" during closing operation.
- 2-button deluxe wall station features independent up/down and light on/off button controls.
- Three-button mini transmitter can control up to six remote accessories.
- Automatic trolley reconnect engages opener automatically after you have used the emergency release.
- System design includes shock absorbing cushion arm to assure that door closes completely even if garage floor heaves in cold weather.
- 100% HomeLink Compatible

SAFETY & SECURITY

- The system automatically monitors itself for malfunctions in relays, electronics and safety functions prior to and during door operation.
- System alerts you to malfunctions with a flashing light and allows the door to open only. However, even with an alert, you can close the door safely and securely using constant pressure on the wall station control button.
- Radio controls with rolling access codes foil code-grabbers from gaining access to your home through the garage door. Every time you operate the door with the remote, the unit automatically chooses a new personal access code.
- If for some reason (i.e. power failure) the door just stops on an object (such as a child) and does not reverse, you can still lift the door and pull the object clear. Quantum openers are designed that if the motor shuts off, the clamping force of the opener is released, unlike other openers whose pressure continues.
- Opener securely locks the door into place in the last two inches of travel by use of a mechanical locking mechanism. Other openers rely on the back-force of the drive unit to provide locking of the door, which is not as effective.
- Security light stays on for 4 minutes to provide safer and easier night entry to garage and home.
- Protection sensors automatically reverse a closing door and stop an operating door when it encounters an obstruction. Sensitivity can be adjusted without hampering normal operation. Since opener produces little vibration, it remains highly sensitive to any contact.
- External "open" "close" limit adjustment for safety and ease of adjustment

Quantum® 3214 1/2 HP Garage Door Opener Specification Sheet

ADDITIONAL FEATURES

- HP-1/2
- Color-black
- Head weight-24.5 lbs
- Volts-120v/60hz
- Lens Cover

DIMENSIONS

- 3214 Unit weight (rail and head)
 - 7ft 50.5 lbs
 - 8ft 52.5 lbs
 - 9 ft 55.5 lbs
 - 10 ft. 57.5 lbs
- Maximum door height: 7-10 ft. heights available for all models
- Lifting rate-9.4" per second all models
- Minimum clearance-2" all models

STANDARD ACCESSORIES

- 3 -button keychain / visor transmitter
- 2-button deluxe wired wall station
- Wired, infrared safety sensors

WARRANTY

- Quantum 3214 has a lifetime-limited warranty on the motor and drive unit, 5 years on other mechanical parts, and 3 years on electronics. See dealer for complete details.