



- NOTES:
1. DOOR MODEL DS75I IS INSULATED DS-75
 2. WHEN USING LOCK BY OTHERS (LBO), EXTENDED THROW SLIDE REQUIRED
 3. TOP DRAFT STOP OPTIONAL
 4. CURTAIN LOCK (CTL) HAND DETERMINED OUTSIDE LOOKING IN
 5. DIMENSIONS SHOWN ARE APPROXIMATE. SEE INSTALL MANUAL FOR EXACT COMPONENT LOCATION
 6. FASTENER SUBSTITUTION MUST BE REVIEWED AND APPROVED BY FACTORY PRIOR TO INSTALL

BRACKET TYPE	A
BEARING BRACKET	4-1/4"
TENSION-PRO BRACKET	5"

OPENING HEIGHT	B
UP TO 6'8" HIGH	16"
FROM 6'8-1/4" TO 8' HIGH	17"
OVER 8' HIGH	18"

WINDLOAD RATING	
MAXIMUM DOOR WIDTH	10'-0"
POSITIVE DESIGN PRESSURE	30PSF
NEGATIVE DESIGN PRESSURE	34PSF

DS-75 WINDLOAD DOOR

CUSTOMER NAME _____

CUSTOMER NUMBER _____

PROJECT NAME _____

PROJECT LOCATION _____

CONTACT _____

PHONE NUMBER _____

FAX NUMBER _____

DATE _____

SALES ORDER NUMBER	DOOR MODEL	QTY	EXACT OPENING SIZE		OUTSIDE CURTAIN COLOR	JAMB TYPE		LH BRACKET TYPE	LOCK OPTIONS		OPTIONAL TOP DRAFT STOP?	OPTIONAL HOOD?	OTHER OPTIONS
			WIDTH	HEIGHT		MAS	STL		WOOD	BEARING			
	DS75	DS75I											