

Instruction Insert

This supplemental installation instruction is to be used as a supplement to the main Installation Instruction and Owner's Manual provided with the door. The instructions included in this document are only those which deviate from the standard installation. All warnings and cautions listed in the main manual are applicable to this supplemental instruction as well.

www.Wayne-Dalton.com

WARNING

- KEEP AWAY FROM HEAT, SPARK AND FLAME.
- USE WITH ADEQUATE VENTILATION.
- PAINT CAN BE IRRITATING TO SKIN. AVOID DIRECT CONTACT WITH SKIN AND EYES. DO NOT INGEST PAINT OR SWALLOW CAP.
- KEEP OUT OF REACH FROM CHILDREN.
- PLEASE REFER TO THE SPECIFIC PAINT PEN MANUFACTURER'S MSDS, FOR FURTHER DETAILS.

1. Surfaces to be touched up should be clean and dry. If needed, clean the area to be repaired as identified in the Cleaning and Painting Your Garage Door section of your Installation Instructions and Owner's Manuals.

2. First, start by identifying your markers. Depending on the door's finish (painted and / or stained), touch up may require one single marker (paint) or the combination of two markers (base & glaze for stain). All markers are clearly identified on the outside of each marker.

USE THE FOLLOWING TO IDENTIFY YOUR MARKER(S):

2a. If Your Door Has Standard Colors: You'll have a single marker and the main color of the door is listed on the outside of the marker.

2b. If Your Door Has Custom Paint Colors: You'll have a single marker (paint): This is for most Custom Painted (non-white or non-stained) Doors such as Custom.

2c. If Your Door Is Fiberglass And Not Stained: You'll have a single marker. The Main color of the door followed by "Metal" will be on the outside of the marker.

2d. If Your Door Is Fiberglass And Has A Custom White Paint: You'll have a single marker. The Main color of the door preceded by "base coat" will be on the outside of the marker.

2e. If Your Door Is Fiberglass And Is Also Stained:

You'll have two different markers.

One Color marker, which has the main color of the door identified on the outside marker.

One Grain Pen marker, which has "Graining Pen" identified on the outside of the marker.

MARKER(S) INSTRUCTIONS:

3. Color marker is to be prepared as follows: Shake the marker back and forth for a minimum of one minute so the internal ball agitates the paint.

NOTE: It is important to fully agitate the paint to avoid paint color match issues.

Relieve the marker pressure by depressing the tip while the marker is in an upright position. To start the flow to the tip, press tip onto cardboard or other paper product until the paint saturates the tip and begins to flow when applied. Do not use a paper towel to wipe the tip.

4. FOR COLOR MARKERS: Use the edge of the tip to minimize the width and the amount paint being applied. Remove any excess paint from the tip and lightly apply the color to the painted surface to fill or cover the scratch and/or abrasion.

NOTE: For best results blend / smear color lightly with finger.

Next, apply only to the area of the repair, and DO NOT apply to any other areas. Additional coat(s) may be needed but try not to apply an excessive amount. Wipe away any excess.

5. GRAINING PEN (THIS IS ONLY APPLICABLE FOR 2 MARKER STAINED SYSTEMS, AS DENOTED IN SECTION 2E.):

Do not apply until base coat is dry, approximately 5 minutes. Using a very light stroke to minimize the width being applied, reconnect the woodgrain lines that were affected by the scratched area. Wipe away any excess using your finger to help blend the woodgrain lines into the existing woodgrain pattern.

6) INSPECTION: Generally, a correct repair may still be visible from 0-2 feet away but should not be visibly noticed at a distance of 5 feet away.