

THERMOSPAN® 200-20

INSULATED SECTIONAL STEEL DOORS



PREMIUM THERMAL EFFICIENCY AND LOW MAINTENANCE

Thermospan® Model 200-20 offers premium thermal efficiency combined with a heavy-duty 20-gauge flush exterior surface. Continuously foamed-in-place insulation and a non-conductive thermal break between the inner and outer skins, making it the ideal door for energy-conscious architects, engineers, contractors, and building owners.

The Thermospan® Series of doors are the only doors in the industry with patented, roll-formed integral struts on each section, making them the most rigid doors available.

*Wayne Dalton uses a calculated door section R-value and U-value for our insulated doors.

» PREMIUM THERMAL QUALITIES
R-VALUE* = 17.50
U-VALUE* = 0.057

» STANDARD SIZES UP TO
24' 2" WIDE AND 16' 1" HIGH

» RUGGED AND DURABLE

» SMOOTH, FLUSH EXTERIOR FINISH

» INTEGRAL STEEL STRUTS
FOR SUPERIOR STRENGTH

» 10K CYCLE SPRINGS STANDARD

THERMOSPAN® 200-20

STANDARD FEATURES OVERVIEW

THERMAL EFFICIENCY

R-VALUE*	17.50 (3.09 K m ² /W)
U-VALUE*	0.057 (.324 W/K m ²)
THERMAL BREAK	Thermoplastic adhesive with rubber seal
AIR INFILTRATION	.07 cfm/ft ²

CONSTRUCTION

SECTION THICKNESS	2" (51 mm)
INTEGRAL STRUTS	Two 1-3/4" struts per section for strength and rigidity
MAX HEIGHT	16'1" (7,366 mm)
MAX WIDTH	24'2" (4,902 mm)
EXTERIOR STEEL	20-gauge
INTERIOR PER SECTION	Roll formed with two 1-3/4" integral struts sealed with polypropylene rib caps
STANDARD SPRINGS	10,000 cycles
INTERIOR COLOR	White
EXTERIOR COLOR	White

CODES AND ASTM STANDARD CLASS

STC (ASTM E 413)	Class 22
OITC (ASTM E 1332)	Class 19
ASTM E 84	Class A
UBC 17-5	Meets
ASTM D 1929	Flash ignition = 734 ° F, Self ignition = 950 ° F

WARRANTY

TERMS	Ten (10) years against cracking, splitting, rust deterioration and delamination. One (1) year against defects in material and workmanship
-------	--

OPTIONS

- Pass door
- Vision lites
- Aluminum full-view sections
- Chain hoist operation
- Motor operation
- Sensing edges
- TruChoice™ Color System
- Photo eyes
- High cycle spring (25k, 50k, 100k)
- 3" Track option
- Solid shafts
- Perimeter weatherseal
- Special track designs
- Mullions

*Wayne Dalton uses a calculated door section R-value and U-value for our insulated doors.

The Thermospan® 200-20 excels in energy efficiency and durability.

With a U-value* of .057 and a R-value* of 17.5, this door outperforms most conventional insulated steel doors, which typically have U-values between .33 and .51.

MATERIALS AND CONSTRUCTION


The Thermospan® 200-20 has a patented manufacturing process with a polyurethane core that is continuously foamed-in-place between the outer and inner skins.

The outer skin of the hot-dipped galvanized, structural quality steel is factory-finished with baked-on corrosion-resistant primer and a white polyester finished coat. The inner skin is also hot-dipped galvanized steel, factory-finished with the same corrosion-resistant primer and polyester finish coat.

An innovative thermal break keeps the interior skin at room temperature, preventing condensation and frost and helping to resist corrosion.

Reinforcement plates are located at all hardware attachment locations. Commercial-grade hot-dipped galvanized hardware also contributes to the this door's long service life.

FINISH OPTIONS



White Smooth
Flush Finish



Thermospan® 200-20 is available with the TruChoice® Color System, Wayne Dalton's custom painting process that offers more than 6,000 colors. See dealer for details.


INSULATED SECTIONAL STEEL DOOR



LITE OPTIONS



Vision lites



Full-view lites

LITE OPTIONS

Joint seal prevents air infiltration and saves energy.


Thermal break separates inner and outer skins so virtually no heat or cold is conducted through section. Pre-painted inner and outer skins for added corrosion resistance.

Solid polyurethane core provides maximum thermal efficiency and adds to quiet operation and strength.

Integral struts Two 1-³/₄" roll-formed struts per section increases rigidity and strength.

Two-inch nominal thickness.

Heavy-duty 20-gauge smooth, flush exterior skin gives the Thermospan 200-20 excellent strength qualities, ideal for large openings.



Wind load options available

GENERAL OPERATING CLEARANCES

TYPE	HEADROOM		SIDEROOM		DEPTH INTO ROOM	CENTER LINE OF SPRINGS	
	2" TRACK	3" TRACK	2" TRACK	3" TRACK	2" AND 3" TRACK	2" TRACK	3" TRACK
Standard Lift Manual 12" R	13"-17"	NA	4.5"	5.5"	Opening Height +18"	Opening Height +12"	N/A
Standard Lift Manual 15" R	15"-20"	16"-21"				Opening Height +13"	Opening Height +14"
Standard Lift Motor Oper. 12" R	15"-20"	NA			Opening Height +66"	Opening Height +12"	N/A
Standard Lift Motor Oper. 15" R	15"-20"	18"-24"				Opening Height +13"	Opening Height +14"
High Lift Manual	High Lift +12"		24" One Side		Opening Height -Lift +30"	Opening Height +Lift +6.5"	Opening Height +Lift +7.5"
High Lift Motor Oper.							
Vertical Lift Manual	Door Height +20"		4.5"	5.5"	18"	Double Door Height +13"	
Vertical Lift Motor Oper.			24" One Side				
Low Headroom Manual	6"-15"	6"-15"	6"	9"	Opening Height +20" to -26"	N/A	
Low Headroom Motor Oper.	9"-17"	9"-17"			Opening Height +66"		


PANEL/SECTION SELECTION GUIDE

DOOR WIDTH	NUMBER OF PANELS	NUMBER OF WINDOWS	DOOR HEIGHT	NUMBER OF SECTIONS
Up to 9'2"	2	2	Up to 8'1"	4
9'3" to 12'2"	3	3	8'-2" to 10'1"	5
12'3" to 16'2"	4	4	10'2" to 12'1"	6
16'3" to 19'2"	5	6	12'2" to 14'1"	7
19'3" to 24'2"	6	7	14'2" to 16'1"	8
24'3" to 28'2"	Call Factory		16'2" and Up	Call Factory

NOTES:

- For low headroom, springs must be rear mount to achieve minimum headroom listed. Front mount torsion headroom depends on drum size, and varies over the range listed. See approval drawing.
- Side-room of 8" required, one side, for doors with chain hoist.
- Headroom depends on drum size, and varies over the range listed. See approval drawing.


TRACK SELECTION GUIDE




STANDARD LIFT




HIGH LIFT
break-away is standard, straight incline is available




ROOF PITCH
standard or high lift



VERTICAL LIFT
break-away is standard, straight incline is available



LOW HEADROOM
rear mount torsion



LOW HEADROOM
front mount torsion



Architect Resource Center

Visit wayne-dalton.com/architect-resource-center to find our Architect Resource Center. In this tool, you will quickly find all of the specifications, drawings and documents you need to complete your project.

Wayne Dalton
COMMERCIAL DOORS

DISTRIBUTED BY:

2501 S. State Hwy 121 Bus., Ste 200
Lewisville, TX 75067

wayne-dalton.com

