



## Dimension Charts for Model 523 Security Shutters

Please be advised that the dimensions provided below are approximations based on standard offerings. If options are added or sideroom and headroom clearances are tight on your projects, please be sure to work with the factory for the most accurate data based on your jobs needs.

### Model 523 Face of Wall Mounted

#### Slat Data

Slat	Opening Width	Standard
523 slat	Up to 20'	.05" aluminum

#### FOW: Headroom Clearance Dimensions

Opening Height	Headroom clearance with compact bottom bar	Headroom clearance with cremone bottom bar
Up to 4' 0"	10 1/2"	12"
4' 1/8" – 8' 0"	11 1/2"	13"
8' 1/8" – 10' 0"	12 1/2"	14"
10' 1/8" – 12' 0"	13 1/2"	15"
12' 1/8" – 14' 0"	14 1/2"	16"

#### Extruded Aluminum Guide Clearance Dimensions

Dimensions	Max Door Opening Width 20'
Guide Width	3.875"
Guide Width + Offset from edge of wall	3.875" + .375" =4.250"
Guide Depth	1.25"
Wall Tube standout req'd with cylinder lock	3"x1.50"



## Dimension Charts for Model 523 Security Shutters

### Model 523 Between Jamb Mounted

#### Slat Data

Slat	Opening Width	Standard
523 slat	Up to 20'	.05" aluminum

#### BJ: Headroom Clearance Dimensions

Opening Height	Headroom clearance with compact bottom bar – above lintel	Headroom clearance with compact bottom bar – under lintel	Headroom clearance with cremone bottom bar – above lintel	Headroom clearance with cremone bottom bar – under lintel
Up to 4'0"	10 1/2"	9"	12"	10 1/2"
4' 1/8" – 8' 0"	11 1/2"	10"	13"	11 1/2"
8' 1/8" – 10' 0"	12 1/2"	11"	14"	12 1/2"
10' 1/8" – 12' 0"	13 1/2"	12"	15"	13 1/2"
12' 1/8" – 14' 0"	14 1/2"	13"	16"	14 1/2"

#### Extruded Aluminum Guide Clearance Dimensions

Dimensions	Max Door Opening Width 20'
Guide Width	3.875"
Guide Depth	1.25"