



Model 9800

												ASCE 7-05			ASCE 7-10				
Option Code	Positive Design PSF	Negative Design PSF	Maximum Size		Functional Size Limitation (480 lb max balance weight)	Revision #	Facer Style Available	Approvals ²		Glazing available ⁵	Source Plant	3-Second Gust Basic Wind Speeds (MPH) ³			3-Second Gust Basic Wind Speeds (MPH) ⁴				
			Width	Height				FBC	TDI			Exposure B Mean Roof Height ≤ 30'	Exposure C Mean Roof Height ≤ 15'	Exposure C Mean Roof Height ≤ 25'	Exposure B Mean Roof Height ≤ 30'	Exposure C Mean Roof Height ≤ 15'	Exposure C Mean Roof Height ≤ 25'	Exposure D Mean Roof Height ≤ 15'	Exposure D Mean Roof Height ≤ 25'
1200	22.90	26.30	9'-0"	10'-0"	9' x 10'	P4	All	FL 10819	GDR-51	Standard SP	Mt. Hope	120	105	100	155	140	130	125	120
1201	31.20	35.80	9'-0"	10'-0"		P4	All	FL 10819	GDR-51	Standard SP	Mt. Hope	140	125	120	180	160	155	146	140
1202	41.00	46.30	9'-0"	10'-0"		P4	All	FL 10819	GDR-51	Standard SP	Mt. Hope	160	146	135	205	185	175	170	160
1220	15.30	17.00	16'-0"	10'-0"	9' < width ≤ 12' wide up to 10' high	P4	All	FL 10819	GDR-51	Standard SP	Mt. Hope	100	90	85	125	115	110	105	100
1221	23.00	25.00	16'-0"	10'-0"		P4	All	FL 10819	GDR-51	Standard SP	Mt. Hope	120	110	105	155	140	135	125	120
1222 Post	34.40	38.30	16'-0"	8'-0"	>12' width up to 8' high	P6	All	FL 10819	GDR-51	Standard SP	Mt. Hope ⁷	150	135	130	190	175	165	160	150

[Post Installation Instructions](#)
[Jamb Connection Supplement](#)
[Track Supplement Chart](#)

- All doors tested for uniform static air pressure per ANSI/DASMA 108 to pressure of 1.5 x design pressure
- FBC - Florida Building Commission, TDI - Texas Department of Insurance
- Above wind speeds based on ASCE 7-05 are applicable for enclosed structures with an importance factor of 1.0 and assume a maximum of 2' of the door is located within the end zone of a structure. Consult a registered Architect or Structural Engineer for applicability for other project specific conditions.
- Above wind speeds based on ASCE 7-10 Category II structure with a maximum of 2' of the door is located within the end zone of a structure. Consult a registered Architect or Structural Engineer for applicability for other project specific conditions.
- Standard SP** - Short panel glazing (Horizontal, Vertical, and V-Groove panels only) is not impact resistant and does not meet the requirements for Wind-Borne Debris Regions.
- Low Head Room track is available.
- Post kit produced in Pensacola. Longer lead times required.
- Wind speeds listed in this guide are provided for reference purposes only. In **ALL** cases the local building authority is the sole and final determiner of the structural and safety requirements, and suitability of the garage door.