

Fire Door Models



DRAWING	MODEL	Max Width	Slat Type	Impact?	Positive Design PSF	Negative Design PSF	FL APPROVAL NUMBER
035-0039	FireStar / Akbar89	10'	Non-Insulated Insulated	Y	44.00	44.00	12354.1
035-0040 035-0041	FireStar / Akbar89	10'	Non-Insulated Insulated	Y	47.00	47.00	12354.2
		12'	Non-Insulated Insulated	Y	37.00	37.00	
		13'4"	Non-Insulated Insulated	Y	31.00	31.00	
		14'9"	Insulated	Y	37.00	37.00	
		16'	Insulated	Y	31.00	31.00	
		16'	Non-Insulated Insulated	N	47.00	47.00	
035-0042	FireStar / Akbar89	16'	Non-Insulated Insulated	Y	37.00	37.00	12354.3
035-0043	FireStar / Akbar89	16'	Non-Insulated Insulated	Y	47.00	47.00	12354.4
		17'6"	Insulated	Y	47.00	47.00	
		20'6"	Insulated	Y	37.00	37.00	
		22'	Insulated	Y	31.00	31.00	
035-0044	FireStar / Akbar89	22'	Non-Insulated Insulated	N	47.00	47.00	12354.5
		28'	Non-Insulated Insulated	N	37.00	37.00	
		28'9"	Insulated	N	37.00	37.00	
		32'9"	Non-Insulated Insulated	N	31.00	31.00	
		33'9"	Insulated	N	31.00	31.00	
035-0045	FireStar / Akbar89	22'	Non-Insulated Insulated	Y	37.00	37.00	12354.6
035-0046	FireStar / Akbar89	22'	Non-Insulated Insulated	Y	55.00	55.00	12354.7